

FLOW TOTALIZER (with analog input 4...20mA)**Signals: 4...20mA (default) - 0...10Vdc (maximum range $\pm 0,1...40mA$ - $\pm 0,1...40Vdc$)****Counting capacity 6 or 8 digits - Sampling 250 ms (medium) - DIN 96x48**

	Suitable for detection of signals from industrial transmitters 4...20mA or 0...10Vdc Programming through 4 button keypad, memorizing in EEPROM Input: count; reset Working temperature -10, +50°C. Flush mounting (template 92 x 45) IP54
	Power supply
0	115Vac 3,3 VA tolerance -10 +10%
1	230Vac 3,3 VA tolerance -10 +10%
2	24Vac 3,3 VA tolerance -10 +10%
3	24Vdc 3,3W tolerance -10 +10%
9	Special
	Suffix
0/S206	6 digits totalizer
2/S206	Counter with 6 digits threshold+ slower
1H1/S206	6 digits totalizer with impulsive reproduction towards relay
0H3/S206	8 digits totalizer+ instantaneous 4 digits
0TH3/S206	8 digits totalizer+ instantaneous 4 digits and analog output
1H38	counter 8 digits + 4 digits with instant playback pulses through relay
1TH38	counter 8 digits + 4 digits with instant playback pulses through relays and analog output
	Galvanic input separation
-	Non
DCI	Input galvanically isolated (useable only with the power 24Vdc)
Z	Special

